



The SDS format adheres to the standards and regulatory requirements of the United States and may not meet regulatory requirements in other countries.

**Bioclear Matrix Systems
Safety Data Sheet – Diamond Wedges**

"DELRIN" ACETAL RESIN/PTFE BLENDS ALL IN SYNONYM LIST DEL012
Revised 20-APR-2007

DEL012

CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Material Identification

"DELRIN" is a registered trademark of DuPont.

Tradenames and Synonyms

"DELRIN" 100AF,
"DELRIN" 500AF, 510MP NC010, 520MP NC010,
"DELRIN" AFDE588,
"DELRIN" DE9266, DE9407, DE9410 NC010, DE9411 NC010,
"DELRIN" DE9413 NC010, DE9415 NC010,
"DELRIN" DE9432

Company Identification

MANUFACTURER/DISTRIBUTOR

Bioclear Matrix Systems
By Dr David Clark
3802 South Warner Street, Suite A
Tacoma, WA 98409
USA

PHONE NUMBERS

Product Information 1-855-71-Clear (25327)
Transport Emergency CHEMTREC: 1-800-424-9300





COMPOSITION/INFORMATION ON INGREDIENTS

Components

Material	CAS Number	%
ACETAL POLYMER		>75
POLYTETRAFLUOROETHYLENE	9002-84-0	<25
STABILIZER		<4
FORMALDEHYDE	50-00-0	<0.005

Components (Remarks)

Material is not known to contain Toxic Chemicals under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372. Additives in this product do not present a respiration hazard unless the product is ground to a powder of respirable size and the dust is inhaled. All dusts are potentially injurious to the respiratory tract if respirable particles are generated and inhaled in sufficiently high concentrations. Good industrial hygiene practices, as with all dusts, should include precautions to prevent inhalation of respirable particles.

HAZARDS IDENTIFICATION

Potential Health Effects

ADDITIONAL HEALTH EFFECTS

Read the datasheet for this product or the molding guide for this resin family.

ACETAL POLYMER

There are no known effects from exposure to the Delrin polymer itself. If overheated, the polymer releases formaldehyde which may cause skin, eye, and respiratory irritation and allergic reactions.

Significant skin permeation and systemic toxicity after contact appears unlikely. There are inconclusive or unverified reports of human sensitization.

POLYTETRAFLUOROETHYLENE (PTFE)

Inhalation of PTFE dust may cause generalized irritation of the nose, throat and lungs with cough, difficulty breathing or shortness of breath.





Heating PTFE above 300 degrees C may liberate a fine particulate fume. Inhalation may produce polymer fume fever, a temporary flu-like condition with fever, chills, nausea, shortness of breath, chest tightness, muscle or joint ache, and sometimes cough and elevated white blood cell count. The symptoms are often delayed 4 to 24 hours after exposure. These signs are generally temporary, lasting 24-48 hours and resolve without further complications. However, some individuals with repeated episodes of polymer fume fever have reported persistent pulmonary effects. Protection against polymer fume fever should also provide protection against any potential chronic effects.

Exposure to decomposition products from PTFE heated above 400 degrees C may cause pulmonary inflammation, hemorrhage or edema. These more serious consequences of exposure may occur from extreme thermal decomposition of PTFE which can liberate fume particles, and toxic gases (carbonyl fluoride, hydrogen fluoride, and other fluorinated gases) especially under conditions of poor ventilation and/or confined spaces. These decomposition products may initially produce chest tightness or pain, chills, fever, nausea, with shortness of breath, cough, wheezing and progression into pulmonary edema. Edema may be delayed in onset and requires medical treatment. In severe cases, if medical intervention is delayed, pulmonary edema may become life threatening. Recovery is generally complete within a few days; in some rare cases, persistent lung function abnormalities have been reported. Compared to nonsmokers, polymer fume fever symptoms appear to be more prevalent and serious in smokers. Smokers must avoid contamination of tobacco with residual polymer from their hands or from fumes, and should wash their hands before smoking.

Significant skin permeation, and systemic toxicity, after contact with the dust appears unlikely. There are no reports of human sensitization from contact with the dust.

If PTFE dusts contact the eye, mechanical irritation with tearing, pain or blurred vision may result.

Individuals with pre-existing diseases of the lungs or cardiovascular system may have increased susceptibility to the reduction in blood oxygen that may develop after excessive exposures to thermal decomposition products.

Carcinogenicity Information

The following components are listed by IARC, NTP, OSHA or ACGIH as carcinogens.





Material	IARC	NTP	OSHA	ACGIH
FORMALDEHYDE	1	X	X	A2

FIRST AID MEASURES

First Aid

INHALATION

No specific intervention is indicated as the compound is not likely to be hazardous by inhalation. Consult a physician if necessary. If exposed to fumes from overheating or combustion, move to fresh air. Consult a physician if symptoms persist.

SKIN CONTACT

The compound is not likely to be hazardous by skin contact, but cleansing the skin after use is advisable. If molten polymer gets on skin, cool rapidly with cold water. Do not attempt to peel polymer from skin. Obtain medical treatment for thermal burn.

EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

INGESTION

No specific intervention is indicated as compound is not likely to be hazardous by ingestion.

FIRE FIGHTING MEASURES

Flammable Properties

Flash Point: Not Applicable

"Delrin" dust cloud ignition temperature is 440 degrees C (824 degrees F).

Like most organic materials in powder form, dust generated from this product may form a flammable dust-air mixture. Potential for a dust explosion may exist. Minimize the generation and accumulation of dust. Keep away from sources of ignition.

Burns with invisible flame. Hazardous gases/vapors produced in fire are carbon monoxide, formaldehyde, hydrogen fluoride (HF), and, carbonyl fluoride.





Extinguishing Media

Water, Foam, Dry Chemical, CO2.

Fire Fighting Instructions

Keep personnel removed and upwind of fire. Wear self-contained breathing apparatus. Wear full protective equipment.

ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Spill Clean Up

Spilled material is a slipping hazard.
Sweep up to avoid slipping hazard.

HANDLING AND STORAGE

Handling (Personnel)

See FIRST AID and PERSONAL PROTECTIVE EQUIPMENT SECTIONS.

Handling (Physical Aspects)


Open container only in well-ventilated area.
Minimize the generation and accumulation of dust.

Storage

Store in a well ventilated area away from heat and sunlight.
Keep container closed to prevent contamination.

PHYSICAL AND CHEMICAL PROPERTIES Physical Data

Form	Film.
Melting Point	175-183 C (347-361 F)
Solubility in Water	Insoluble
Odor	Slight formaldehyde
Specific Gravity	>1





STABILITY AND REACTIVITY

Chemical Stability

Stable at normal temperatures and storage conditions.

Conditions to Avoid

Maintain polymer melt temperatures below 230 C (446 F) . Avoid prolonged exposure at or above the recommended processing temperatures.

Incompatibility with Other Materials

Incompatible with strong acids and bases (decomposes forming formaldehyde) and strong oxidizing agents. At melt temperatures, acetal resins are incompatible with halogenated polymers such as PVC and PVDC and any elastomers containing halogenated polymers. Even small amounts of such contaminants can cause sudden and spontaneous formaldehyde gas formation. Workplace fume concentrations well above threshold levels are a likely result. Unsafe pressurization of equipment, e.g., extruders, molds, can also result.

Decomposition

Decomposition of this material depends on the length of time it is exposed to elevated temperatures. At the recommended processing temperature of 210-220 C (410-428 F), decomposition should not be significant until after 30 minutes. Decomposition may be accelerated by contaminants, pigments, and/or other additives.

Autoclaving with pressurized steam may lead to a rapid decomposition and should be done for only minimum amounts of time.

COOL COMPLETELY BEFORE OPENING the autoclave.

Hazardous gas/vapor produced is formaldehyde.

Polymerization

Polymerization will not occur.

TOXICOLOGICAL INFORMATION

Animal Data

Delrin

Inhalation 6 hour LC50: > 22,000 mg/m³ in rats

Oral LD50: > 11,000 mg/kg in rats

Delrin is not a skin irritant, and is not a skin sensitizer in animals.





ECOLOGICAL INFORMATION Ecotoxicological Information

AQUATIC TOXICITY:

No information is available. Toxicity is expected to be low based on insolubility in water. Do not discharge to streams, ponds, lakes or sewers.

DISPOSAL CONSIDERATIONS

Waste Disposal

Preferred options for disposal are (1) recycling, (2) incineration with energy recovery, and (3) landfill. The high fuel value of this product makes option 2 very desirable for material that cannot be recycled, but incinerator must be capable of scrubbing out acidic combustion products. Treatment, storage, transportation, and disposal must be in accordance with applicable federal, state/provincial, and local regulations.

TRANSPORTATION INFORMATION

Shipping Information

Not regulated in transportation by DOT/IMO/IATA.

REGULATORY INFORMATION

U.S. Federal Regulations

TSCA Inventory Status : In compliance with TSCA Inventory requirements for commercial purposes.

State Regulations (U.S.)

STATE RIGHT-TO-KNOW

No substances on the state hazardous substances list, for the states indicated below, are used in the manufacture of products on this Safety Data Sheet, with the exceptions indicated.

SUBSTANCES ON THE PENNSYLVANIA HAZARDOUS SUBSTANCES LIST PRESENT AT A CONCENTRATION OF 1 % OR MORE (0.01% FOR SPECIAL HAZARDOUS SUBSTANCES)- None known.





WARNING - SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM- Formaldehyde.

SUBSTANCES ON THE NEW JERSEY WORKPLACE HAZARDOUS SUBSTANCE LIST PRESENT AT A CONCENTRATION OF 1% OR MORE (0.1% FOR SUBSTANCES IDENTIFIED AS CARCINOGENS, MUTAGENS OR TERATOGENS)- None known.

OTHER INFORMATION

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

Responsibility for SDS : REGULATORY AFFAIRS
 DUPONT ENGINEERING POLYMERS
 Address : CHESTNUT RUN PLAZA 713
 WILMINGTON, DE 19880-0713
 Telephone : 302-999-4257

Indicates updated section.

This information is based upon technical information believed to be reliable. It is subject to revision as additional knowledge and experience is gained.

End of SDS

